# **Data Sheet**



# Coaxial Panel Connector 23\_SMA-50-0-52/199\_N

### **Description**

Straight panel receptacle jack, flange mount

Interface standards
IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50~\Omega \\ \text{Interface frequency max.} & 18~\text{GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 500
Weight 0.0026 kg

**Environmental Data** 

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -65 °C to 125 °C compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

# **Related Documents**

Outline drawing DOU-00011333
Catalogue drawing DCA-00010571

## **Ordering Information**

Single package 23\_SMA-50-0-52/199\_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.